



## ZINSSER® B-I-N TURBO

# THE PERFECT AEROSOL SOLUTION FOR PRIMING

- 4x more coverage than traditional spray primers
- Sticks to all surfaces, even ceramic tiles and glass
- Ideal for new construction, water, fire and smoke damage

# ZINSSER® B-I-N TURBO

## DESCRIPTION

The ZINSSER® TURBO SPRAY SYSTEM creates a spray fan that is up to 25cm wide, giving you 4x more coverage for the same time than traditional spray primers. B-I-N® is ideal for new construction, water, fire and smoke damage, remodelling and restoration. B-I-N® sticks to all surfaces, even ceramic tiles and glass. Use on any interior wood, concrete, drywall and non galvanised metal. Replace severely charred substrates and remove loose soot and other contaminants with a dry chemical sponge or duster. Prime damaged surfaces with B-I-N® to block smoke stains, water stains and seal odours.

## DOPORUČENÉ POUŽITÍ

**Interior:** new and previously painted drywall, cured plaster/cement based coatings, wood (pine, fir, cedar, redwood, plywood), metal (aluminum, steel, stainless steel, copper), vinyl, PVC, fiberglass, cured masonry (stucco, concrete block, poured concrete, brick). Blocks stains and odours resulting from water & fire damage, seals stains from dark colours, grease, rust, creosote, asphalt, crayon, lipstick, graffiti, markers, knots, sap streaks, tannin bleed, etc.

**Sealing:** B-I-N seals unpainted or porous surfaces so topcoat paints have better coverage. It fills and binds wood fibres to create a smooth, sealed surface with "enamel holdout" so fewer coats of paint are needed. Note that very porous surfaces may require two coats and may reduce square foot coverage of the product.

**Stain Killing:** B-I-N is the ultimate interior stain killing primer. One coat will effectively block stains, including water, nicotine, ink, graffiti, crayon, marker, rust and smoke stains so they won't bleed into the topcoat. Some stains require a second coat. Recommended for permanently sealing of heavy fire and water stains.

**Odours:** B-I-N seals smoke stains and odours caused by fires or tobacco. It also seals urine and other animal odours from smelling.

**Glossy Surfaces:** B-I-N can be used as an adhesion primer on smooth surfaces without sanding or deglossing. Wall covering: B-I-N may be used to prime existing, soundly adhered, non-porous wall coverings to hide patterns/dark colours prior to painting.

## TECHNICAL DATA

Úroveň lesku při 60°:	5%
Obsah pevných látek v hmotnosti:	25,99%
Obsah pevných látek v objemu:	11,47%

## DRY TIMES BY 20° C/RH 50%

Dotykem suché:	15 minutes
Suchý nátěr:	45 minutes
Plně vytvrzené:	1 - 3 days

## TEORETICKÁ SPOTŘEBA

This can covers approximately 3m² dependent upon surface profile / porosity.

## PRAKTICKÁ SPOTŘEBA

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## PŘÍPRAVA POVRCHU

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper adhesive or any contamination that may interfere with adhesion. If unsure, always wash surface with a household ammonia and water solution or an appropriate cleaning solution. Remove any unsoundly adhered coatings. Sand any remaining paint film edges smooth with the surface. Lightly sand exposed exterior wood with 80 to 100 grit sandpaper to remove loose or weathered wood fibers. Attempt to remove existing stains by washing, sanding, scraping, etc. Kill exterior mildew with a suitable mildew killer. Bare wood that has been exposed for more than 4 weeks should be lightly sanded or abraded to remove weathered wood fibres. Remove mould and mildew before painting with a suitable biocidal wash. Rinse well. For commercial buildings and schools follow appropriate guidelines for mould removal.

## NÁVOD K POUŽITÍ

For interior use and spot exterior use only. Use at room temperature in a well-ventilated area - avoid high humidity. Ensure the surface to be painted is clean, completely dry (moisture content <12%), sound and free from any dirt, residues or any surface contamination that will affect the performance of the primer. Shake can vigorously until ball inside can rattles. Contact Zinsser® if mixing ball fails to rattle. DO NOT STRIKE THE CAN. Turn upside down and continue shaking for one minute – shake occasionally during use. Spray 25-30cm from object with short 'dusting' strokes. Surface may be painted in 45 minutes. For further information please contact our Technical Services Department.

## PODMÍNKY POUŽITÍ

Apply only when temperature is between -5°C and 25°C and relative humidity is below 85%. Special precautions should be taken during the surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. When dry-sanding avoid dust inhalation by wearing a suitable protective face mask.

## POZNÁMKY

If valve clogs, remove spray tip and rinse in methylated spirit. To clear spray for future use, turn can upside down and spray until clear gas is emitted. Wipe up splatters before they dry with methylated spirit. LIMITATIONS: Not suitable for full exterior use. Not suitable for use on floors or areas subjected to foot traffic.

## DOBA POUŽITELNOSTI

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 4 and 27°C.

last\_updated: 02/07/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu