



## ZINSSER® ALLCOAT INTERIOR MATT

# Primer and finish in one for all interior surfaces

- Multi surface application.
- Ultra durable formula.
- Scuff & scrub resistant†
- Mould & algae resistant coating#
- Streak-free finish.



# ZINSSER® ALLCOAT INTERIOR MATT

## BESCHREIBUNG

ALLCOAT® Interior Matt is an ultimate performance all surface paint. Designed for the long term decoration of timber, metal, masonry, uPVC, concrete, plasterboard, plaster, walls and ceilings.

## EMPFOHLENE VERWENDUNG

ALLCOAT® Interior Matt is a primer and finish in one for all interior surfaces, with premium properties and performance. This product is designed for the durable finish of wood, metal, masonry, PVC, concrete, drywall, plaster, walls and ceilings. A scrub-resistant, stain-resistant, even matt finish with perfect and uniform covering power. For use on, among others, PVC, ceramic tiles, aluminium, copper, steel, galvanised steel, wood, plasterboard, white plaster, concrete, walls and ceilings in any interior.

## EMPFOHLENES SYSTEM

two-coat system - no primer needed

## TECHNISCHE DATEN

Dichte (g/cm <sup>3</sup> ):	1,2 - 1,4
Glanzgrad bei 60°:	<3%
Glanzgrad bei 85°:	w5%
Feststoffgehalt in Gewicht:	60%
Feststoffgehalt in Volume:	50%
Widerstand gegen Nassreibung (EN 13300):	Klasse 1 (< 5 µm Abrieb bei 200 Hüben)

## TROCKENZEITEN BEI 20°C/RF 50%

Klebfrei:	1 hr
Überstreichbar:	2 hrs
Durchgehärtet:	5 - 7 days

## THEORETISCHE ERGIEBIGKEIT

10-12m<sup>2</sup>/litre per coat

## PRAKTISCHE ERGIEBIGKEIT

In practice, hiding power depends on many factors, such as the porosity and roughness of the substrate and material loss during application.

## UNTERGRUNDVORBEREITUNG

Surfaces must be clean, dry, sound and free of dirt, dust, grease, wax, wallcovering adhesive, soap film, loose paint or other surface contamination. Clean surfaces with thoroughly with a proprietary degreaser / cleaner in accordance with the manufacturers instructions. Ensure surface is completely dry before painting, with a maximum moisture content of 16%. Remove all existing mould and mildew before painting using an appropriate mould removal solution. If you are concerned about mould and mildew growth on other surfaces and/or unseen places, contact a mould removal specialist. Follow appropriate guidelines for mould removal. Remove all rust back to clean, bare ferrous metal, if signs of rusting are evident apply an anti-corrosive metal primer in accordance with manufacturers recommendations. Check for satisfactory paint adhesion by cutting an "X" with a razor blade in the old paint film. Apply cellophane tape firmly over the "X" and pull tape quickly away. If old paint releases, remove by scraping. Sand rough areas and remove dust. New/Bare Plaster: For optimum results seal first with a suitable sealer. Special precautions should be taken during surface preparation of pre-1960 paint surfaces as they may contain harmful lead. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Two-coat System – No Priming Required!  
Seal all stains with an appropriate Zinsser stain blocking primer where required before applying ALLCOAT® Interior Matt.

## HINWEISE ZUR VERARBEITUNG

Stir thoroughly before use. Apply with a synthetic bristle brush, medium pile roller or sprayer. For airless spraying, use a .017 tip and high medium (2000-2600 PSI) pressure. Apply when air and surface temperatures are between 10°-32°C and humidity is less than 80%.

## ANWENDUNGSBEDINGUNGEN

Apply when air and surface temperatures are between 10°-32°C and humidity is less than 80%.

## VERDÜNNUNG & ANWENDUNG: PINSEL

Apply with a synthetic bristle brush

## VERDÜNNUNG & ANWENDUNG: ROLLER

Use a medium pile roller

## VERDÜNNUNG & ANWENDUNG: AIRLESS SPRITZEN

Tip: .017 / Pressure: 2000-2600 PSI.

## REINIGUNG DER ARBEITSGERÄTE / SPRITZER

Clean application tools, spatters and spills immediately with warm water and liquid detergent; rinse with water. Follow equipment manufacturer's directions to clean spray equipment. Remove dried ALLCOAT® Interior Matt with a household cleaner; rinse with water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings

## BEMERKUNGEN

ALLCOAT® Interior Matt can be tinted to all colours via the CS2 tinting system using the appropriate tint base. Multiple containers of tinted paint should be intermixed (boxed) to ensure colour uniformity.

ALLCOAT® Interior Matt is not intended for application to floors or any surface subject to water immersion or prolonged contact including shower enclosures, saunas or steam rooms. If using in areas of high humidity e.g. bathrooms allow at least 24 hours before subjecting the applied coating to humidity from the shower/bath. It is recommended that a trial area is first coated to ensure the product is satisfactory to individual requirements before full surface application

## SICHERHEITSDATEN

VOC-Gehalt:	2 g/L
VOC-Gehalt Fertigmischung:	2 g/L
VOC-Kategorie:	IIA/a
VOC-Grenzwert:	30g/l
Grenelle:	c
Bemerkungen für Sicherheit:	Consult the Safety Data Sheet and the safety information on the paint can.

## LAGERFÄHIGKEIT

At least 2 years from production date in unopened original packaging, if stored in dry, well-ventilated areas, out of direct sunlight, at temperatures between 5 and 32°C.

Ausgabedatum: 02/05/2024

**Verfügbare Farben und Packungsgrößen:** Bitte beziehen Sie sich auf die jeweilige Produktseite auf [www.rust-oleum.eu](http://www.rust-oleum.eu) für eine Übersicht der aktuell verfügbaren Farben und Größen verpacken.

**Haftungsausschluss:** Die hierin enthaltenen Informationen wurden nach bestem Wissen wahrheitsgetreu und präzise und im guten Glauben zusammengestellt. Wir übernehmen aber keine Haftung. Wir gehen davon aus, dass sich der Anwender eigenverantwortlich über die Eignung unserer Produkte für seine individuelle Zweckbestimmung informiert hat. Rust-Oleum Europe übernimmt keinerlei Haftung für Folgeschäden oder mittelbare Schäden. Die Produkte müssen gelagert, gehandhabt und unter Bedingungen verwendet werden, die den Empfehlungen von Rust-Oleum Europe entsprechen, die in der neuesten Ausgabe des Produktdatenblatts angegeben sind. Der Anwender muss sicherstellen, dass er die neueste Ausgabe besitzt. Die neuesten Ausgaben des Produktdatenblatts können kostenlos auf [www.rust-oleum.eu](http://www.rust-oleum.eu) heruntergeladen oder bei unserer Kundendienstabteilung angefordert werden. Rust-Oleum Europe behält sich das Recht vor, die Eigenschaften seiner Produkte ohne vorherige Ankündigung zu ändern.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu