



ZINSSER® ALLCOAT INTERIOR MATT

Primer and finish in one for all interior surfaces

- Multi surface application.
- Ultra durable formula.
- Scuff & scrub resistant†
- Mould & algae resistant coating#
- Streak-free finish.

ZINSSER® ALLCOAT INTERIOR MATT

BESKRIVELSE

ALLCOAT® Interior Matt is an ultimate performance all surface paint. Designed for the long term decoration of timber, metal, masonry, uPVC, concrete, plasterboard, plaster, walls and ceilings.

ANBEFALT BRUK

ALLCOAT® Interior Matt is a primer and finish in one for all interior surfaces, with premium properties and performance. This product is designed for the durable finish of wood, metal, masonry, PVC, concrete, drywall, plaster, walls and ceilings. A scrub-resistant, stain-resistant, even matt finish with perfect and uniform covering power. For use on, among others, PVC, ceramic tiles, aluminium, copper, steel, galvanised steel, wood, plasterboard, white plaster, concrete, walls and ceilings in any interior.

ANBEFALT SYSTEM

two-coat system - no primer needed

TEKNISKE DATA

Tetthet:	1,2 - 1,4
Glansgrad ved 60°:	<3%
Glansgrad ved 85°:	w5%
Tørrstoffinnhold i vekt:	60%
Tørrstoffinnhold i volum:	50%
wet_scrub_resistance:	wsr_c1

TØRKETID VED 20°C/50% RELATIV LUFTFUKTIGHET

Støvtørr:	1 hr
Overmalbar:	2 hrs
Herdetid:	5 - 7 days

TEORETISK FORBRUK

10-12m²/litre per coat

PRAKTISK FORBRUK

In practice, hiding power depends on many factors, such as the porosity and roughness of the substrate and material loss during application.

KLARGJØRING AV OVERFLATE

Surfaces must be clean, dry, sound and free of dirt, dust, grease, wax, wallcovering adhesive, soap film, loose paint or other surface contamination. Clean surfaces with thoroughly with a proprietary degreaser / cleaner in accordance with the manufacturers instructions. Ensure surface is completely dry before painting, with a maximum moisture content of 16%. Remove all existing mould and mildew before painting using an appropriate mould removal solution. If you are concerned about mould and mildew growth on other surfaces and/or unseen places, contact a mould removal specialist. Follow appropriate guidelines for mould removal. Remove all rust back to clean, bare ferrous metal, if signs of rusting are evident apply an anti-corrosive metal primer in accordance with manufacturers recommendations. Check for satisfactory paint adhesion by cutting an "X" with a razor blade in the old paint film. Apply cellophane tape firmly over the "X" and pull tape quickly away. If old paint releases, remove by scraping. Sand rough areas and remove dust. New/Bare Plaster: For optimum results seal first with a suitable sealer. Special precautions should be taken during surface preparation of pre-1960 paint surfaces as they may contain harmful lead. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Two-coat System – No Priming Required! Seal all stains with an appropriate Zinsser stain blocking primer where required before applying ALLCOAT® Interior Matt.

BRUKSANVISNING

Stir thoroughly before use. Apply with a synthetic bristle brush, medium pile roller or sprayer. For airless spraying, use a .017 tip and high medium (2000-2600 PSI) pressure. Apply when air and surface temperatures are between 10°-32°C and humidity is less than 80%.

PÅFØRINGSBETINGELSER

Apply when air and surface temperatures are between 10°-32°C and humidity is less than 80%.

PÅFØRING & FORTYNNING: PENSEL

Apply with a synthetic bristle brush

PÅFØRING & FORTYNNING: RULLE

Use a medium pile roller

PÅFØRING & FORTYNNING: LUFTFRI SPRØYTE

Tip: .017 / Pressure: 2000-2600 PSI.

RENGJØRING AV UTSTYR/SPILL

Clean application tools, splatters and spills immediately with warm water and liquid detergent; rinse with water. Follow equipment manufacturer's directions to clean spray equipment. Remove dried ALLCOAT® Interior Matt with a household cleaner; rinse with water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings

MERKNADER

ALLCOAT® Interior Matt can be tinted to all colours via the CS2 tinting system using the appropriate tint base. Multiple containers of tinted paint should be intermixed (boxed) to ensure colour uniformity.

ALLCOAT® Interior Matt is not intended for application to floors or any surface subject to water immersion or prolonged contact including shower enclosures, saunas or steam rooms. If using in areas of high humidity e.g. bathrooms allow at least 24 hours before subjecting the applied coating to humidity from the shower/bath. It is recommended that a trial area is first coated to ensure the product is satisfactory to individual requirements before full surface application

SIKKERHETSDATA

VOC nivå:	2 g/L
VOC ferdigblandet:	2 g/L
VOC kategori:	IIA/a
VOC grense:	30g/l
grenelle:	c
Merknader angående sikkerhet:	Consult the Safety Data Sheet and the safety information on the paint can.

HOLDBARHET

At least 2 years from production date in unopened original packaging, if stored in dry, well-ventilated areas, out of direct sunlight, at temperatures between 5 and 32°C.

Utstedt dato: 02/05/2024

Tilgjengelige farger & størrelse på forpakninger: Vennligst referer til den respektive produktsiden på www.rust-oleum.eu for en oversikt over tilgjengelige farger og størrelse på forpakninger.

Ansvarsfraskrivelse: Så langt vi kjenner til er informasjonen i dette dokumentet korrekt og nøyaktig. Den er gitt i god tro, men uten garanti. Brukeren må selv avgjøre om våre produkter er egnet for hans/hennes bestemte formål. Ikke under noen omstendigheter skal Rust-Oleum Europe bli gjort ansvarlig for indirekte eller tilfældige skader. Produktene må lagres, håndteres og påføres under forhold som tilfredsstiller Rust-Oleum Europes anbefalinger som er detaljert beskrevet i den siste oppdaterte kopien av produktdatabladet. Brukerne er selv ansvarlige for at de har den siste oppdaterte kopien. De siste oppdaterte kopier av produktdatabladet er tilgjengelig, og kan lastes ned gratis fra www.rust-oleum.eu, eller de kan fås ved forespørsel til vår kundeserviceavdeling. Rust-Oleum Europe forbeholder seg retten til å endre egenskapene til produktene sine uten forhåndsvarsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu