



ZINSSER[®] BIN ADVANCED

Synthetic Shellac Primer

- Excellent stain blocker
- Low odor; soap and water clean up
- Seals tannin, knots and sap streaks
- Seals cigar, cigarette & nicotine odors
- Seals severe water stains, fire & smoke damage

ZINSSER® BIN ADVANCED

DESCRIPTION

B-I-N® Advanced Synthetic Shellac Primer is a synthetic shellac-based primer sealer that provides excellent stain blocking for whole-surface interior priming and exterior spot priming. It combines fast dry time, low odor, excellent hide and stain blocking for new construction, remodeling and fire and water restoration. B-I-N Advanced may be used under and over any latex or oil-based architectural paint.

Use B-I-N Advanced to prime all types of bare or painted interior surfaces including wood, drywall, cured plaster, masonry, galvanized metal and PVC. B-I-N Advanced has excellent adhesion to dense, glossy surfaces such as enamel paints and varnishes, paneling, laminates, glass and ceramic tile without the need for sanding or de-glossing.

UTILISATION RECOMMANDÉE

SPOT PRIMING: B-I-N Advanced is excellent for use in spot priming exterior surfaces. B-I-N Advanced effectively seals knots and sap streaks. Note: Spot prime only under high hiding paints or prime the entire surface with Zinsser® Bulls-Eye 1-2-3® after spot priming.

SEALING: B-I-N Advanced penetrates and seals porous surfaces and dries to a smooth finish with excellent enamel holdout. It can be used as an effective primer to improve coverage and sheen consistency of the finish coat.

STAIN BLOCKING: B-I-N Advanced will effectively block stains from water, nicotine, grease, oil, soot, rust, mildew, tannin, crayon and lipstick. It also provides an excellent odor barrier to block odors from fire damage, smoke, cigar & cigarettes, pet urine, and fireplaces. To block odors while preserving the original surface color, use B-I-N Clear Advanced.

APPEARANCE: B-I-N Advanced is white but may be tinted to off-white and pastel shades by adding no more than 7 mL of universal colorant per L to improve the hiding power of the topcoat.

LIMITATIONS: B-I-N Advanced is not recommended for full service use on exterior applications, for excessively humid interior areas or surfaces subject for immersion or prolonged contact with water. Do not mix or intermix B-I-N Advanced with other oilbase or water-base products.

DONNÉES TECHNIQUES

Densité (g/cm³):	1.29
Niveau de brillance:	Mat
Extrait sec en poids:	51.2%
Extrait sec en volume:	36.9%

TEMPS DE SÉCHAGE À 20°C/HR 50%

Au toucher:	25 minutes
Recouvrable:	45 minutes
Dur à cœur:	7 days

EPAISSEUR DE FILM HUMIDE RECOMMANDÉE

100-137 µm

EPAISSEUR DE FILM SEC RECOMMANDÉE

37.5-50 µm

CONSUMMATION THÉORIQUE

7.5-10 m²/L/coat

CONSUMMATION PRATIQUE

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

PRÉPARATION DE SURFACE

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper, adhesive or any contamination that may interfere with adhesion. If unsure, wash surface with an appropriate cleaning solution or solvent and rinse

thoroughly. Remove any peeling and/or unsound coatings. Sand any remaining paint film edges smooth. When priming over stained areas, first attempt to remove as much of the stain as possible by washing, sanding, scraping, etc. Allow surface to dry completely before priming.

PRÉCAUTIONS D'UTILISATION

Thoroughly mix or shake to ensure any settled pigment is re-dispersed before using. If thinning is required, add no more than 10 ounces of water per gallon. In most cases only one coat is necessary to prime most surfaces. If excessive absorption occurs over very porous substrates a second coat may be necessary. For best results, prime entire surface before painting.

CONDITIONS D'APPLICATION

Apply only when air, material, and surface temperatures are between 10-32°C and the relative humidity is less than 85%.

APPLICATION & DILUTION: BROUSSE

High quality brush

APPLICATION & DILUTION: ROULEAU

3/8" nap roller

APPLICATION & DILUTION: PISTOLET AIRLESS

Use a 0.015-0.017" tip at 1700-2200 psi. Follow manufacturer's instructions when using spray equipment. Provide adequate ventilation at all times.

NETTOYAGE DU MATERIEL / ECLABOUSSURES

Clean up spills and paint drips with warm soap and water. Wipe up splatters before they dry. Follow the equipment manufacturer's directions to clean spray equipment.

REMARQUES

For knots and stain blocking, allow 2 hours to dry. When sealing water stains, some stain may appear in the primer film as it dries. The stain is locked and will not bleed into the topcoat.

DONNÉES DE SÉCURITÉ

Teneur en COV:	<100 g/L
COV prêt à l'emploi:	30 g/l
Catégorie COV:	A/g
Limite COV:	30 g/l (2010)
Remarques pour la sécurité:	Consult Safety Data Sheet and Safety Information printed on the can.

DURÉE DE VIE

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 4 and 32°C.

Date d'émission: 21/09/2021

Couleurs et conditionnements disponibles: Reportez-vous à la page produit concernée sur www.rust-oleum.eu pour avoir un aperçu des couleurs et des tailles d'emballage actuellement disponibles.

Notion de responsabilité: Les informations communiquées ici sont véridiques et exactes et sont fournies de bonne foi au meilleur de nos connaissances, mais sans garantie. Il est estimé que l'utilisateur se sera assuré lui-même de la compatibilité de nos produits avec son usage particulier. Rust-Oleum Europe ne sera en aucun cas tenue pour responsable quant aux dommages consécutifs ou indirects. Les produits doivent être stockés, manipulés et appliqués conformément aux conditions respectant les recommandations de Rust-Oleum Europe détaillées dans le dernier exemplaire de la fiche technique du produit. Il incombe aux utilisateurs de veiller à disposer de l'exemplaire actuel. Les dernières versions de la fiche technique du produit sont disponibles gratuitement et peuvent être téléchargées sur www.rust-oleum.eu ou sur demande adressée à notre département Service à la clientèle. Rust-Oleum Europe se réserve le droit de modifier les propriétés de ses produits sans avis préalable.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu