



ZINSSER® COVER STAIN®

Primer-Sealer Stain Killer

- Fast Drying – recoat in less than 2 hours
- Designed for interior and exterior surfaces
- High hiding formula blocks most stains, including nicotine
- Excellent for sealing water-soluble tannin bleed on cedar and redwood

ZINSSER® COVER STAIN®

BESKRIVELSE

Multi-applicable solvent-based stain-blocking primer and sealer. Ideal for interior / exterior use. Paintable in only 2 hours. Can be finished with any solvent-based or water-based top coat.

ANBEFALT BRUK

Recommended for application to fire, smoke and water damaged surfaces, including: interior ceilings, walls, doors, trim, cabinets, furniture and related paintable surfaces.

Exterior siding, fascia, soffits, trim, doors, walls, foundations, railings, and related paintable surfaces that may have been damaged by fire, smoke or water.

Cover Stain is recommended for application to the following fire, smoke or water damaged substrates:

Interior: New or previously painted, cured plaster and cement-based coatings, wood (including pine, fir, cedar, redwood, plywood), metal (including aluminum, iron, steel, and copper), vinyl, PVC, masonry (including stucco, concrete block, poured concrete, and brick).

Exterior: New or previously painted wood (including pine, fir, cedar, redwood, and pressure-treated wood), hard-board, metal (including aluminum, iron, steel and copper), vinyl, PVC.

TEKNISKE DATA

Glansgrad ved 60°:	12/13%
Tørstoffinnhold i vekt:	74,5%
Tørstoffinnhold i volum:	56,3%

TØRKETID VED 20°C/50% RELATIV LUFTFUKTIGHET

Støvtørr:	35 minutes
Overmalbar:	2 hours
Herdetid:	4 to 7 days

TEORETISK FORBRUK

9,8 m² per litre

PRAKTISK FORBRUK

Coverage may vary depending upon method of application and surface porosity.

KLARGJØRING AV OVERFLATE

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper, adhesive or any contamination that may interfere with adhesion. If unsure, always wash surface with an appropriate ammoniated cleaning solution or solvent (do not use tri sodium phosphate based cleaners). Remove any peeling and / or unsound coatings. Sand any remaining paint film edges smooth. Lightly sand exposed exterior wood with 80 to 100 grit sandpaper to remove loose or weathered wood fibers and mill glaze. When priming over stained areas, first attempt to remove as much of the stain as possible by washing, sanding, scraping, etc. Allow surface to dry completely before priming. Countersink exposed nail heads, spot-prime and fill all nail holes and gouges. Wire brush rusty areas. Spot prime knots and sap streaks with B-I-N Primer-Sealer before whole surface priming with Cover Stain.

BRUKSANVISNING

Shake or stir before using. In most cases only one coat is necessary to prime most surfaces. If excessive absorption occurs over very porous substrates a second coat may be necessary. Spot priming is recommended only under high hiding topcoat paints. For best results prime entire surface before painting. Allow to come to room temperature before use. Use in a well ventilated area avoiding high humidity.

PÅFØRINGSBETINGELSER

Apply when air and surface temperatures are between 5°C and 32°C and humidity is less than 85%. Note that temperature and humidity directly affect dry time of the product.

Higher temperatures and lower humidity will accelerate the dry time while lower temperatures and higher humidity will slow down the dry time.

PÅFØRING & FORTYNNING: PENSEL

Apply with a natural or synthetic bristle brush. Cover Stain is designed to be used without thinning.

PÅFØRING & FORTYNNING: RULLE

Cover Stain is designed to be used without thinning.

PÅFØRING & FORTYNNING: LUFTFRI SPRØYTE

Follow manufacturer's instructions when using spray equipment. Airless spraying- use a 0.015" to 0.017" tip at 1800 to 2200 P.S.I. Cover Stain is designed to be used without thinning.

RENGJØRING AV UTSTYR/SPILL

Clean up spills and drips with a rag soaked in mineral spirits or paint thinner. If spills or drips have dried, use paint remover. Application tools may be cleaned using paint thinner – rinse tools repeatedly in mineral spirits or paint thinner until solvent runs clear and tool is thoroughly cleaned.

MERKNADER

Standard white Cover Stain may be tinted to off white and pastel shades by adding no more than 60 ml. solvent based colorants per 5 liter. Deep Tint may be tinted to mid to dark tones by adding no more than 250 ml per 5 liter.

Cover Stain is not intended for application to floors, decks, roof surfaces or any surfaces subject to immersion or prolonged contact with water

SIKKERHETSDATA

VOC nivå:	maximum 350 g/l
VOC kategori:	II A/g
VOC grense:	350 g/l (2010)
Merknader angående sikkerhet:	Consult product Safety Data Sheet

HOLDBARHET

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 4 and 27°C.

Utstedt dato: 04/02/2025

Tilgjengelige farger & størrelse på forpakninger: Vennligst referer til den respektive produktsiden på www.rust-oleum.eu for en oversikt over tilgjengelige farger og størrelse på forpakninger.

Ansvarsfraskrivelse: Så langt vi kjenner til er informasjonen i dette dokumentet korrekt og nøyaktig. Den er gitt i god tro, men uten garanti. Brukeren må selv avgjøre om våre produkter er egnet for hans/hennes bestemte formål. Ikke under noen omstendigheter skal Rust-Oleum Europe bli gjort ansvarlig for indirekte eller tilfældige skader. Produktene må lagres, håndteres og påføres under forhold som tilfredsstiller Rust-Oleum Europes anbefalinger som er detaljert beskrevet i den siste oppdaterte kopien av produktdatabladet. Brukerne er selv ansvarlige for at de har den siste oppdaterte kopien. De siste oppdaterte kopier av produktdatabladet er tilgjengelig, og kan lastes ned gratis fra www.rust-oleum.eu, eller de kan fås ved forespørsel til vår kundeserviceavdeling. Rust-Oleum Europe forbeholder seg retten til å endre egenskapene til produktene sine uten forhåndsvarsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu