



ZINSSER® COVERS UP™

Stain blocking primer and finishing coat in one

- Matt white finish, for indoor use
- Primer and finishing coat in one
- Blocks stains from water, nicotine and smoke
- Ideal for retouching a ceiling
- Quick drying and low odour

ZINSSER® COVERS UP™

BESKRIVELSE

COVERS UP™ is an acrylic, solvent-based stain blocking primer and ceiling paint in one. This low odour and quick drying primer ensures a matt white finish that matches the colour of most ceiling tiles and white ceiling paints. The vertical aerosol is easy to use. Ideal for retouching a ceiling. For indoor use.

ANBEFALET BRUG

For indoor use. Apply as a primer / finish to interior acoustic ceiling tiles or painted ceilings, light fixtures, HVAC ductwork and vents, overhead pipes and conduit, or anywhere an overhead high hiding stain sealing primer or spot finish is needed. New, primed or previously painted ceiling tiles, drywall, cured plaster, cement, stucco, wood (pine, fir, birch, oak and plywood), aluminum, iron, steel and galvanized metal, PVC, glossy laminates and other interior surfaces.

TØRRETIDER VED 20°C/50% RELATIV LUFTFUGTIGHED

Berøringsør: 30 minutes (@ 20°C)
Genbehandlingør: 2 hours

TEORETISK FORBRUG

1.5 m²/aerosol

PRAKTISK FORBRUG

Practical coverage depends on many factors such as porosity and roughness of the substrate, type of application and material losses during application

FORBEHANDLING AF OVERFLADEN

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper adhesive or any contamination that may interfere with adhesion. If unsure, always wash surface with a household ammonia and water solution, appropriate cleaning solution, or solvent (Do not use tri sodium phosphate based cleaners). Remove any unsoundly adhered coatings. Sand any remaining paint film edges smooth with the surface. Attempt to remove existing stains by washing, sanding, scraping, etc.

BRUGSANVISNING

Use at room temperature in a well-ventilated area - avoid high humidity. Shake can until ball inside rattles, then continue shaking for one minute. Repeat shaking periodically during use. Test spray pattern on scrap surface before using. Spray 25-30 cm from surface. Apply with short 'dusting' strokes. When finished, clean valve by holding can upside down and spraying until clear gas comes out. To clear clogged spray tip, remove from can and clean with pin.

ANVENDELSESBETINGELSER

Use at a temperature of 4 - 32°C at a humidity <85%.

RENGØRING AF UDSYR/SPILD

Clean spills and drips with a rag dampened in mineral spirits.

BEMÆRKNINGER

COVERS UP™ is not intended for application to floors, decks, roof surfaces or any surface subject to immersion or prolonged contact with water.

SIKKERHEDSDATA

VOC-kategori: /
Bemærkninger om sikkerhed: Consult Safety Data Sheet and Safety Information printed on the aerosol.

HOLDBARHED

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 25°C.

Udstedelsesdato: 11/03/2025

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europas anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu