



## ZINSSER® PEEL STOP

**Peel Stop® is a clear, flexible bridging sealer.**

- Extend the life of problem surfaces
- Seals and bridges cracking and checking
- Glues down cracks and gaps under edges of old paint
- Binds chalky surfaces Interior and exterior use
- Recoat in 2 hours Soap and water cleanup Flexible/breathable



# ZINSSER® PEEL STOP

## DESCRIPTION

Peel Stop® is a clear, flexible bridging sealer for surfaces where peeling, flaking, dusting or chalking is a problem. Use indoors or out to form a breathable membrane over questionable or faulty substrates. Peel Stop® tightly bonds to old paint and problem areas forming a sound surface for new paint. Peel Stop® forms a tough acrylic film that stays flexible and helps prevent peeling by letting moisture escape. A clear sealer, Peel Stop® works like nothing else to stop peeling problems on old or new surfaces. Recommended uses: Peel Stop® prevents peeling, blistering, checking, cracking and flaking on wood siding and trim, yellow pine, rough sawn cedar, textured plywood, chalking or powdering, concrete and concrete block, stucco and galvanized gutters.

## ODPORÚČANÉ POUŽITIE

Recommended for application to problem interior / exterior painted surfaces that exhibit chalking, alligatoring, cracking, flaking, and peeling. Substrates – Peel stop is recommended for application to the following substrates: Exterior Surfaces – Previously painted wood siding, windows, doors, fences, and trim; dry and denatured timber; metal gutters and downspouts; masonry siding, walls and foundations (inc. cured concrete, stucco, concrete block, brick, vinyl and galvanized siding, etc.) Interior Surfaces – Previously painted drywall, plaster, cement, concrete, or stucco walls and ceilings; wood doors, windows, baseboards and trim.

## TECHNICAL DATA

Hustota (g/cm <sup>3</sup> ):	1.05
Úroveň lesku:	Satin
Obsah pevných látok v hmotnosti:	21.6%
Obsah pevných látok v objeme:	19.3%

## DRY TIMES BY 20° C/RH 50%

Na dotyk suché:	1 hour
Suché na manipuláciu:	2 hours
Suchý na opätovné natieranie:	2 hours
Úplne vytvrdené:	7 - 10 days

## ODPORÚČANÁ HRúbKA MOKRÉHO FILMU

83 µm

## ODPORÚČANÁ HRúbKA SUCHÉHO FILMU

20 µm

## TEORETICKÁ SPOTREBA

7.4 - 9.8 m<sup>2</sup>/l

## PRAKTICKÁ VÝDATNOSŤ

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## PRÍPRAVA POVRCHU

Thorough surface preparation is very important. Surfaces should be clean, dry, sound and free of dust, dirt, grime, grease, oil, wax, mould, wallpaper adhesive, or any contamination that may interfere with adhesion. If unsure, always wash surface with an appropriate cleaning solution or solvent. Surfaces must be thoroughly scraped and sanded to remove all poorly adhered paint. Lightly sand exposed wood to remove loose fragments. Dull glossy painted areas with sandpaper. Application Requirements- Spot prime areas where paint has been scraped or sanded off. In most cases only one coat is necessary. Excessively porous surfaces may require a second coat.

## NÁVOD NA POUŽITIE

Stir thoroughly before use.

## PODMIENKY APLIKÁCIE

Apply when air and surface temperatures are between +10° and +32°C and humidity is less than 80%. Lower temperature and higher humidity will prolong dry time of the product. If conditions do not permit prompt drying, allow PEEL STOP to dry overnight before priming or painting. Do not apply PEEL STOP if rain is expected and primer or topcoat cannot be applied before rain occurs.

## APLIKÁCIA A RIEDENIE: ŠTETEC

Apply with brush. Back brush to work PEEL STOP into cracks and edges of old paint. For best brushing performance use quality synthetic bristle brushes. Natural bristle brushes are not recommended for use with the product. Do not thin.

## APLIKÁCIA A RIEDENIE: VALEC

Apply with roller. Back roll to work PEEL STOP into cracks and edges of old paint. Do not thin.

## ČISTENIE ZARIADENIA / POSTRIEKANIE

Clean fresh spills and drips with a wet cloth or rag. Wash application tools in warm, soapy water and rinse well. Follow manufacturer's instructions when cleaning spray equipment. Use Zinsser BIN Brush Cleaner to remove dried paint from bristle.

last\_updated: 27/10/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu

# ZINSSER® PEEL STOP

## POZNÁMKY

Selection Data Generic Type – Vinyl resin, water-based, clear, Interior / exterior binding primer Tinting - Tinting is not recommended. Thinning- Thinning is not recommended. Drying Time- At normal temperatures Peel Stop will dry in one hour and may be primed or painted in two hours. Note: Peel Stop that has seeped under the edges of remaining paint layers or has filled minute cracks may take longer to dry than material on exposed surfaces. Priming & Top coating- Any water based or alkyd primer or paint may be used over Peel Stop. As Peel Stop is clear, we recommend priming with Zinsser Bulls Eye® 1-2-3 or Zinsser Cover-Stain®, followed by a coat of quality water based or alkyd paint to assure optimum results. Limitations- Peel Stop is formulated to help prolong the adhesion of existing paint coatings and is not intended as a substitute for proper surface preparation or for use on surfaces where paint failure results from chronic or excessive moisture intrusion. Repair any source of moisture intrusion before attempting to repaint. Ongoing paint failure may require complete removal of the existing coating system. Not for use on floors, exterior decks or surfaces subject to immersion or prolonged contact with water. Warranty- Peel Stop is guaranteed to perform as claimed when applied according to the label directions to a properly prepared surface. Directions are as complete as possible but cannot encompass all conditions, applications, and / or surfaces beyond manufacturer's control. The contents of the container are warranted to be free from any other defect for 2 years from the date of manufacture. All warranties and guarantees are limited to refund or replacement of product used with proof of purchase. No other warranty or guarantee is expressed or implied.

## SAFETY DATA

Úroveň VOC:	0,1 g/l
VOC readymix:	0,1 g/l
Kategória VOC:	A/h
Limit VOC:	30 g/l
Poznámky k bezpečnosti:	WARNING! Do Not Take Internally. May cause gastrointestinal irritation. If swallowed call a doctor or poison control center. Avoid contact with with eyes and skin. May cause eye and skin irritation. In case of eye contact flush eyes with water for at least 15 minutes. Use with adequate ventilation. KEEP OUT OF REACH OF CHILDREN. Consult Safety Data Sheet and Safety Information printed on the can.

## SKLADOVATEĽNOSŤ

Minimum of 2 years from date of production in unopened cans.

last\_updated: 27/10/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu