



ZINSSER® PERMA-WHITE SATIN

High performance interior paint

- Protection of the dried coat against fungal degradation
- Self-priming
- Good adhesion on glossy and hard-to-paint surfaces
- Easy application properties
- Durable, washable, moisture resistant finish



ZINSSER® PERMA-WHITE SATIN

BESKRIVELSE

High performance acrylic interior paint uniquely formulated to beautify and protect interior surfaces while protecting the dried coat against fungal degradation for. Scrubbable – Class 1 Wet Scrub Rating (ISO 11998).

ANBEFALT BRUK

For application to interior walls, wall cavities, ceilings, trim, doors, tiles and related paintable surfaces. Ideal for bathrooms, basements, kitchens, laundry rooms, closets, locker rooms, hot tub rooms, enclosed porches and pool areas or any interior where mold & mildew is a concern. Great for institutional or commercial use in schools, hospitals, hotels, nursing homes, restaurants, athletic facilities, etc.

TEKNISKE DATA

Tetthet:	1,42
Glansgrad:	Satinert
Glansgrad ved 60°:	Satin: 18-23%
Glansgrad ved 85°:	Satin: 47-53%
Tørrstoffinnhold i vekt:	54%
Tørrstoffinnhold i volum:	38%
wet_scrub_resistance:	wsr_c1

TØRKETID VED 20°C/50% RELATIV LUFTFUKTIGHET

Støtør:	30 minutes
Overmalbar:	2 h
Herdetid:	7 - 10 days

ANBEFALT VÅTFILMYKKELSE

100 - 150 µm

ANBEFALT TØRRFILMYKKELSE

40 - 60 µm

TEORETISK FORBRUK

7 - 10 m²/l

PRAKTISK FORBRUK

Practical coverage depends on many factors such as porosity and roughness of the substrate, type of application and material losses during application.

KLARGJØRING AV OVERFLATE

Surfaces must be clean, sound and free of dirt, dust, grease, wax, wall covering adhesive, soap film, loose paint or other surface contamination. Remove all existing mold and mildew before painting.

If you are concerned about mould and mildew behind walls, underneath flooring, in ventilation systems or other unseen areas, contact a professional who specializes in mould and mildew remediation. For commercial buildings and schools follow appropriate guidelines for mould removal. Clean surfaces with a solution of a teacup household bleach per litre water or a quality biocidal wash.

Stains: rust, tannin, grease, mold & mildew and other stains should be blocked with the appropriate stain killing primer sealer such as Zinsser B-I-N, B-I-N Aqua, Bulls Eye 123 Plus or 123. When priming over stained areas, first attempt to remove as much of the stain as possible by washing, sanding, scraping, etc.

BRUKSANVISNING

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

PÅFØRINGSBETINGELSER

Apply when air and surface temperatures are between 10 - 32°C and humidity is less than 80%.

PÅFØRING & FORTYNNING: PENSEL

Use synthetic bristle brush. Do not dilute.

PÅFØRING & FORTYNNING: RULLE

Do not dilute.

PÅFØRING & FORTYNNING: LUFTFRI SPRØYTE

Nozzle: 017 - 013.

Pressure: 140 - 180 bars.

Do not dilute.

PÅFØRING & FORTYNNING: FORSTØVNINGSSPRØYTE

If necessary diluted with water up to 10%.

RENGJØRING AV UTSTYR/SPILL

Water.

MERKNADER

Apply second coat 2 hours or longer after the first. Scrape-resistance over glossy surfaces develops in 5 to 7 days as Perma-White cures. Do not scrub the new coating for seven days.

Product is not intended for application to floors or any surface subject to water immersion or prolonged contact with water including shower enclosures, saunas or steam.

Product does not protect against food borne or disease-causing bacteria.

2 coats are required for proper performance and mould & mildew-resistance.

In the situation where PERMA-WHITE should be tinted on smooth and non porous substrates, first prime with Zinsser Bulls Eye 123 or 123 Plus.

SIKKERHETSDATA

VOC nivå:	50 g/l
VOC ferdigblandet:	50 g/l
VOC kategori:	A/i
VOC grense:	140 g/l
Merknader angående sikkerhet:	Consult Safety Data Sheet and Safety Information printed on the can.

HOLDBARHET

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 35°C. To prevent product from skinning over close container after each use. Keep lid tightly closed during storage. Protect from freezing.

Utstedt dato: 11/03/2025

Tilgjengelige farger & størrelse på forpakninger: Vennligst referer til den respektive produktsiden på www.rust-oleum.eu for en oversikt over tilgjengelige farger og størrelse på forpakninger.

Ansvarsfraskrivelse: Så langt vi kjenner til er informasjonen i dette dokumentet korrekt og nøyaktig. Den er gitt i god tro, men uten garanti. Brukeren må selv avgjøre om våre produkter er egnet for hans/hennes bestemte formål. Ikke under noen omstendigheter skal Rust-Oleum Europe bli gjort ansvarlig for indirekte eller tilfældige skader. Produktene må lagres, håndteres og påføres under forhold som tilfredsstiller Rust-Oleum Europes anbefalinger som er detaljert beskrevet i den siste oppdaterte kopien av produktdatabladet. Brukerne er selv ansvarlige for at de har den siste oppdaterte kopien. De siste oppdaterte kopier av produktdatabladet er tilgjengelig, og kan lastes ned gratis fra www.rust-oleum.eu, eller de kan fås ved forespørsel til vår kundeserviceavdeling. Rust-Oleum Europe forbeholder seg retten til å endre egenskapene til produktene sine uten forhåndsvarsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu