



## ZINSSER® PERMA-WHITE SATIN

# High performance interior paint

- Protection of the dried coat against fungal degradation
- Self-priming
- Good adhesion on glossy and hard-to-paint surfaces
- Easy application properties
- Durable, washable, moisture resistant finish



# ZINSSER® PERMA-WHITE SATIN

## BESKRIVNING

High performance acrylic interior paint uniquely formulated to beautify and protect interior surfaces while protecting the dried coat against fungal degradation for. Scrubbable – Class 1 Wet Scrub Rating (ISO 11998).

## REKOMMENDERAD ANVÄNDNING

For application to interior walls, wall cavities, ceilings, trim, doors, tiles and related paintable surfaces. Ideal for bathrooms, basements, kitchens, laundry rooms, closets, locker rooms, hot tub rooms, enclosed porches and pool areas or any interior where mold & mildew is a concern. Great for institutional or commercial use in schools, hospitals, hotels, nursing homes, restaurants, athletic facilities, etc.

## TEKNISK DATA

Densitet:	1,42
Glansnivå:	Satin
Glansnivå vid 60°:	Satin: 18-23%
Glansnivå vid 85°:	Satin: 47-53%
Torrsubstansvikt:	54%
Torrsubstansvolym:	38%
wet_scrub_resistance:	wsr_c1

## TORKTIDER VID 20°C/RELATIV LUFTFUKTIGHET 50%

Beröringstorr:	30 minutes
Övermålningsbar:	2 h
Fullt härdad:	7 - 10 days

## REKOMMENDERAD VÄTFILMSTJOCKLEK

100 - 150 µm

## REKOMMENDERAD TORRFILMSTJOCKLEK

40 - 60 µm

## TEORETISK FÖRBRUKNING

7 - 10 m<sup>2</sup>/l

## PRAKTISK FÖRBRUKNING

Practical coverage depends on many factors such as porosity and roughness of the substrate, type of application and material losses during application.

## YTFÖRBEREDELSE

Surfaces must be clean, sound and free of dirt, dust, grease, wax, wall covering adhesive, soap film, loose paint or other surface contamination. Remove all existing mold and mildew before painting.

If you are concerned about mould and mildew behind walls, underneath flooring, in ventilation systems or other unseen areas, contact a professional who specializes in mould and mildew remediation. For commercial buildings and schools follow appropriate guidelines for mould removal. Clean surfaces with a solution of a teacup household bleach per litre water or a quality biocidal wash.

Stains: rust, tannin, grease, mold & mildew and other stains should be blocked with the appropriate stain killing primer sealer such as Zinsser B-I-N, B-I-N Aqua, Bulls Eye 123 Plus ou 123. When priming over stained areas, first attempt to remove as much of the stain as possible by washing, sanding, scraping, etc.

## BRUKSANVISNING

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

## APPLICERINGSFÖRHÅLLANDEN

Apply when air and surface temperatures are between 10 - 32°C and humidity is less than 80%.

## APPLICERING OCH SPÄDNING: PENSEL

Use synthetic bristle brush. Do not dilute.

## APPLICERING OCH SPÄDNING: ROLLER

Do not dilute.

## APPLICERING OCH SPÄDNING: AIRLESSPRUTA

Nozzle: 017 - 013.

Pressure: 140 - 180 bars.

Do not dilute.

## APPLICERING OCH SPÄDNING: TRYCKLUFTSSPRUTA

If necessary diluted with water up to 10%.

## RENGÖRING AV UTRUSTNING/SPILL

Water.

## ANMÄRKNINGAR

Apply second coat 2 hours or longer after the first. Scrape-resistance over glossy surfaces develops in 5 to 7 days as Perma-White cures. Do not scrub the new coating for seven days.

Product is not intended for application to floors or any surface subject to water immersion or prolonged contact with water including shower enclosures, saunas or steam.

Product does not protect against food borne or disease-causing bacteria.

2 coats are required for proper performance and mould & mildew-resistance.

In the situation where PERMA-WHITE should be tinted on smooth and non porous substrates, first prime with Zinsser Bulls Eye 123 or 123 Plus.

## SÄKERHETSDATA

VOC-nivå:	50 g/l
VOC färdigmix:	50 g/l
VOC-kategori:	A/i
VOC-gräns:	140 g/l
Anmärkingar om säkerhet:	Consult Safety Data Sheet and Safety Information printed on the can.

## HÅLLBARHET

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 35°C. To prevent product from skinning over close container after each use. Keep lid tightly closed during storage. Protect from freezing.

Utgivningsdatum: 11/03/2025

**Tillgängliga färger och förpackningsstorlekar:** Se respektive produktsida på [www.rust-oleum.eu](http://www.rust-oleum.eu) för en översikt över tillgängliga färger och förpackningsstorlekar.

**Förbehåll:** Informationen i detta produktdatablad är korrekt så långt vi känner till och ges i god tro men utan garanti. Vi förutsätter att användaren självständigt har tagit ställning till lämpligheten av våra produkter för hans eller hennes egna syften. Under inga omständigheter är Rust-Oleum Europe ansvarigt för indirekta skador eller följdsador. Produkterna ska förvaras, hanteras och användas under förhållanden som överensstämmer med Rust-Oleum Europes rekommendationer i den senaste utgåvan av produktdatabladet. Det är användarens ansvar att säkerställa att han/hon har den aktuella utgåvan. Senaste utgåvan av produktdatabladet kan erhållas kostnadsfritt från [www.rust-oleum.eu](http://www.rust-oleum.eu) eller vår kundtjänst. Rust-Oleum Europe förbehåller sig rätten att ändra egenskaperna i sina produkter utan föregående avisering.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM s-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)